

# REPEATERS (BDAs)

## UHF REPEATERS Band Selective

FIPLEX BDA45 Series of Band Selective Repeaters are cost effective and reliable solutions designed to extend and improve the coverage area of UHF analog / digital telecommunication systems. Band Selective Repeaters amplifies in both directions, uplink and downlink a continuous bandwidth, software adjustable. The presence of a FIPLEX Repeater provides to the system with a high channel occupancy rate, since coverage is extended beyond site coverage. Typical applications of this line of repeaters are indoor situations such as tunnels, buildings, subways, and outdoor scenarios such as stadiums, rural areas and dense urban areas.



### Features & Benefits

**Auto diagnostics:** Compact Repeaters are equipped with a microprocessor module that controls the unit operational parameters. This self check capability provides an instantaneous alarm output under failure situation, via local LEDs. Microprocessor module verifies main board status, PA status, power supply status, intermediate filters status, battery backup status, open door and temperature levels.

**Antenna isolation control:** Units are provided with a built in, microprocessor controlled, antenna isolation control. This feature verifies the real antenna to antenna isolation (donor antenna to service antenna/s), and adjust the maximum available repeater gain to avoid antenna feedback and oscillation, increasing system reliability.

**Control:** Compact Repeaters can be controlled locally via USB, and can be remote controlled using FIPLEX OMS (Operation and Maintenance Software) via wireless connection. In both situations, local and remote, Compact Repeaters parameters can be adjusted (UL gain, DL gain, ON/OFF, etc) and alarms can be supervised (amplifiers status, PA status, power supply status, battery backup status, door open and temperature)

**Manual gain control:** Uplink and Downlink gain levels can be adjusted to meet system planning requirements. Both chains (UL and DL) can be adjusted independent, digitally, in 1dB steps. This gain control can be done locally via USB or can be done remote via wireless connection (FIPLEX OMS).

**Automatic Gain Control (AGC):** Repeaters are equipped with Automatic Gain Control (AGC) that acts in both Uplink and Downlink chains independent. The presence of an AGC allows a maximum power operation with low intermodulation generation, and provides a lineal operation that ensures a high quality signals amplification.

**Battery backup:** Repeaters can be powered with AC or DC. Battery backup mode is available for continuous operation in case of AC or Power Supply failure, or when no AC is available.

**Weatherproof enclosure:** Units are equipped with IP65 enclosures, to allow a simple and easy installation procedure since no special weather protection is required. Standard fixing method is Wall and Pole mounting.

DOC BD095.04 • 14092009



### Repeaters (BDA)

Tower Mounted Amplifiers (TMA)

Products for IDEN

Products for Tetra / Tetrapol

Transmitters Combiners

Duplexers

R.F. Components

Broadcasting

## RF Specifications

Frequency range	400 – 520 MHz
Type	Band Selective Repeater
Passband BW, min	0.2 to 5 MHz, software adjustable
Downlink to Uplink separation, min	5.0 MHz min, 10MHz typ
Gain, maximum	80 dB
Passband ripple	+/- 2.0 dB
Gain, manual control	30dB range, digitally controlled in 1dB steps
Antenna isolation control, gain adjustment	0 to 30 dB
AGC range	0 to 30 dB
Composite output power, DL	<b>BDA45S-2B4LC</b> +40 dBm (10 W) <b>BDA45S-2B2LC</b> +30 dBm (1 W)
Composite output power, UL	+25 dBm
IM generation	< -13dBm
Noise figure, in dB	3.0 max at maximum output power
Impedance	50Ω
Group delay	6uS max
Connectors	N(f) as standard
VSWR at operating frequencies	1.5:1 max

## Supervising Specifications

Self diagnostic platform	Microprocessor based
Alarms	Yes, amplifiers status, power amplifiers status, power supply failure, battery backup failure, temperature, AGC, RF overload, poor antenna isolation, door open.
Local management and supervising	Local access via USB
Remote management and supervising	Remote access via wireless modem, option RC-G (FIPLEX OMS)
RoHS compliance	Yes

## Electrical & Mechanical Specifications

AC Supply	110/220 VAC
DC Supply	12 VDC
Housing	IP65
Temp range	-30 to +60 °C
Size, WxDxH, in mm	390 x 390 x 100
Weight	18 Kgs
Mounting	Wall mounting as standard. Option PK for pole mounting.
Fiber optic links	Available as option FO, intended for multiple repeaters configuration and/or long distance runs.

Model	Pass band BW, in MHz	UL – DL separation, in MHz	Gain, in dB	Power out, DL, in dBm
<b>BDA45S-2B2LC</b>	2.0	5.0 min	80	+30
<b>BDA45S-2B4LC</b>	2.0	5.0 min	80	+40

### Fiplex Argentina

Ph. +54 351 456 8263 · Fax +54 351 456 2507 · S. Cabral 1242, C.P. 5006, Córdoba, Argentina · E-mail: info@fiplex.com

### Fiplex USA

Ph. +1 305 884 8991 · Fax +1 305 8844041 · 7331 NW 54 St-Miami FL 33166-USA · E-mail: info@fiplex.com

### Fiplex Europe

Ph. +34 91 662 58 66 · Fax +34 91 662 34 08  
E-mail: europe.sales@fiplex.com